



Liquid-O-Ring®\*

YOUR SUPER CENTER FOR OVER 1,000 TOP PERFORMANCE  
PRODUCTS SERVING INDUSTRIES WORLDWIDE

WWW.OILCENTER.COM

856



COBRA-COAT®  
COILED TUBING PROTECTION

GEAR OILS

MOTOR OILS

HYDRAULIC OILS

PIPE COATINGS

THREAD SEALANTS

BEARING GREASES

SPECIALTY  
GREASES

THREAD  
COMPOUNDS

SUCKER ROD  
COATINGS

OUTSIDE  
PRESERVATIVES

WIRELINE  
GREASE SEALS

CLEANERS &  
DEGREASERS

PIPE STORAGE  
COMPOUNDS

RUST &  
CORROSION  
INHIBITORS

THREAD LOCKING  
COMPOUNDS

VALVE  
LUBRICANTS &  
SEALANTS

TOOL JOINT &  
DRILL COLLAR  
COMPOUNDS

## PRODUCT DESCRIPTION

856 Cobra-Coat® is specifically used to prevent corrosion to the OD and ID of coiled tubing while in storage or between jobs. Cobra-Coat® will provide a light protective film that will displace water and adhere to metal surfaces. Cobra-Coat® can be pumped through the ID of the coiled tubing string as a pill between slugs of water to leave a thin, oil-soluble film that will protect the tube against damaging corrosive elements left in the tubing. As an OD coating Cobra-Coat® can be applied with standard air or airless spray equipment.

Cobra-Coat® is ready-to-use, and for most applications does not require dilution. It will dry to a tacky film that is water repellent to provide protection even when the reel is stored outside.

## BENEFITS

- Oil-Soluble
- Protects against corrosion
- Adheres to metal surfaces
- Can be used on OD and ID
- Sprayable
- Won't peel or flake off

## APPLICATION

For best results, tubing should be clean and free of rust, scale or dirt, however Cobra-Coat® will provide adequate protection when applied on top of these elements.

Cobra-Coat® can be pumped through the ID of the coiled tubing string or can be applied with standard air or airless spray equipment as an OD coating. Cobra-Coat® will completely set up in 2 hours. Dust and dirt can be easily wiped off without affecting film.

## TYPICAL OBSERVATIONS

Color	Brown
Appearance	Liquid
Odor	Petroleum Solvent
Density, lb/gal @ 77°F (25°C)	7.30
Specific Gravity, @ 77°F (25°C)	0.875
Flash Point, ASTM D-56	145°F (63°C)
Boiling Point	>300°F (>149°C)
Solubility in Water	Insoluble
Shelf Life (unopened container)	One Year

## RELATED PRODUCTS

856AG Cobra-Coat® Arctic Grade



© 2012, BALMAR LLC Made in U.S.A.

**WARRANTY** Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by

**BALMAR LLC**

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:

LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

\*Registered trade name of  
Oil Center Research, Inc. 12/27/16

The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, [www.oilcenter.com](http://www.oilcenter.com), or contact your Account Representative for the most current information relating to this product.