

DAM10K

DAMING SEAL 10,000 Wireline Grease

PRODUCT DESCRIPTION

DAM10K is the latest cost effective product to meet the industry's most demanding needs. This product is unmatched by other manufacturers in performance and protection against the corrosive effects of oilfield brines and chemicals. Available in a broad viscosity range, DAM10K is the answer for moderate well conditions, where standard grade grease seal is required. DAM10K meets the needs for all braided line operations including logging, perforating, and pump down operations.

BENEFITS

- Additive package
- Cost effective
- Adhesive and cohesive properties
- Available in standard ISO viscosities

APPLICATION

DAM10K is recommended as a pump down grease for braided wireline, cables, and wire rope. Apply DAM10K using grease injector control heads and cable lubricators.

TYPICAL OBSERVATIONS

Color	Golden Yellow
Texture	Tacky Liquid
Odor	Mild
Density, lb/gal @ 77°F (25°C)	7.2–7.3
Specific Gravity @ 77°F (25°C)	0.87–0.88
Flash Point, ASTM D-92	390°F (198°C)
Rust Preventive Test, ASTM D-3603 @ 140°F (60°C)	Pass
Temperature Range	75°F to 130°F 24°C to 60°C
Shelf Life (unopened container)	Four years